

**FOR CHEMICAL EMERGENCY
DURING TRANSPORTATION ONLY**

Call INFOTRAC

1-800-535-5053

24 hrs. per day, 7 days per week

MATERIAL SAFETY DATA SHEET

ABBREVIATIONS: NA = NOT APPLICABLE
ND = NOT DETERMINED
NE = NOT ESTABLISHED

HEALTH =1
FLAMMABILITY =2
REACTIVITY =1
PERSONAL PROTECTION =

SECTION 1

PRODUCT NAME: **MASON SEAL**

PRODUCT TYPE: WATER REPELLANT

REVERE PRODUCTS
4529 INDUSTRIAL PARKWAY
CLEVELAND, OHIO 44136
TELEPHONE: (216) 573-7100

EMERGENCY TELEPHONE (800) 535-5053
INFOTRAC

DATE PREPARED: 2/17/94
PREPARED BY: GSS
D.O.T. SHIPPING CLASS: COMBUSTIBLE LIQUID

WFO/A

=====

SECTION 2 - INGREDIENTS

=====

CHEMICAL NAME	CAS NO.	OSHA PEL	ACGIH TLV	% WT
MINERAL SPIRITS	64742-48-9	100 PPM	100 PPM	90

* SUBJECT TO REPORTING REQUIREMENTS OF SARA TITLE III SECTION 313, 40 CFR 372

=====

SECTION 3 - PHYSICAL DATA

=====

BOILING POINT (°F): 318-383
VAPOR PRESSURE: 2.6 mm Hg
VAPOR DENSITY: 4.8 (AIR=1)
SOLUBILITY IN WATER: <0.1
APPEARANCE/ODOR: COLORLESS, CLEAR LIQUID, HYDROCARBON ODOR

SPECIFIC GRAVITY: .80
MELTING POINT: N/A
EVAPORATION RATE (BUAC=1): 0.13
pH: N/A

=====

SECTION 4 - FIRE AND EXPLOSION DATA

=====

FLASH POINT (METHOD USED): 105 F (TCC) FLAMMABILITY LIMITS: LEL 0.7 UEL 6.0

EXTINGUISHING MEDIA: WATER, FOAM, CARBON DIOXIDE, DRY CHEMICAL

SPECIAL FIRE FIGHTING PROCEDURES: NONE KNOWN

UNUSUAL FIRE FIGHTING AND EXPLOSION HAZARDS: BURNING LIQUID MAY FLOAT ON WATER AND SPREAD.