

Conq-R-Dust (aerosol)

(I) 160-CODU-A

S.C. Johnson Wax  
Racine, Wisconsin 53403-5011  
Phone: (414) 631-2777  
Emergency Phone: (800) 228-5635  
Extension 092  
International Emergency Phone:  
Extension 092

4=Very High  
3=High  
2=Moderate  
1=Slight  
0=Insignificant

| HAZARD RATING  |      |
|----------------|------|
| HMIS           | NFPA |
| 1 Health       |      |
| 4 Flammability |      |
| 0 Reactivity   |      |

**MATERIAL SAFETY DATA SHEET****SECTION I-PRODUCT IDENTIFICATION**

|                                                 |                                 |                                |                                          |                                                                     |
|-------------------------------------------------|---------------------------------|--------------------------------|------------------------------------------|---------------------------------------------------------------------|
| PRODUCT NAME:<br><b>CONQ-R-DUST PRESSURIZED</b> |                                 |                                |                                          | PRODUCT CODE:<br><b>14750-5</b>                                     |
| CHEMICAL OR COMMON NAME:<br><b>NA</b>           | DATE ISSUED:<br><b>01/07/94</b> | SUPERSEDES:<br><b>03/19/93</b> | MSDS SECTIONS WITH CHANGES:<br><b>XI</b> | PREPARED BY:<br><b>Terry A. Meyers</b><br><b>Chemical Info. Adm</b> |

**SECTION II-INGREDIENT INFORMATION**

| INGREDIENTS                                                                        | WEIGHT % | EXPOSURE LIMIT                       |
|------------------------------------------------------------------------------------|----------|--------------------------------------|
| [NJ] Light Naphthenic Distillate<br>(CAS# 64741-44-2)                              | 10-20    | 5mg/m3 (ACGIH TLV-TWA)<br>(OSHA PEL) |
| Isoparaffinic Hydrocarbon Solvent<br>(CAS# 64742-48-9)                             | 7-12     | 300 PPM-EXXON RECOMMENDED            |
| [PA,NJ,MA] Isobutane (CAS# 75-28-5)                                                | 5-10     | NE                                   |
| Water (CAS# 7732-18-5)                                                             | 55-65    | NA                                   |
| [PA,NJ,MA] Propane (CAS# 74-98-6)                                                  | 5-10     | 1000 ppm OSHA PEL                    |
| See Regulatory Information (Section XII) for explanation of bracketed information. |          |                                      |

**SECTION III-PHYSICAL DATA**

|                                                               |                                        |
|---------------------------------------------------------------|----------------------------------------|
| APPEARANCE/ODOR: Clear, slightly yellow mist with banana odor | SPECIFIC GRAVITY (H2O=1): 0.9          |
| VAPOR PRESSURE (mm Hg): ND                                    | PERCENT VOLATILE BY VOLUME (%): NA     |
| SOLUBILITY IN WATER: Negligible                               | VAPOR DENSITY (Air=1): ND              |
| FREEZING POINT (°F): NA                                       | BOILING POINT (°F): ND                 |
| pH: NA                                                        | EVAPORATION RATE (Butyl Acetate=1): NA |
| VOC (as packaged, minus H2O): ND                              | THEORETICAL VOC (lb/gal): ND           |

**SECTION IV-FIRE AND EXPLOSION INFORMATION**

|                                                                                                                                                                                                              |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| FLASH POINT (°F) (Method Used): under 20 (TCC) (propellant)                                                                                                                                                  |
| FLAMMABLE LIMITS: ND                                                                                                                                                                                         |
| EXTINGUISHING MEDIA: Foam. CO2. Dry Chemical. Water Fog.                                                                                                                                                     |
| SPECIAL FIREFIGHTING PROCEDURES: Normal fire fighting procedures may be used. Fight fire from maximum distance or protected area. Cool and use caution when approaching or handling fire-exposed containers. |

# MATERIAL SAFETY DATA SHEET

Page 2

S.C. Johnson Wax  
1525 Howe Street  
Racine, Wisconsin 53403

CONQ-R-DUST PRESSURIZED

Product Number: 14750

Serial Number: 5

## SECTION IV-FIRE AND EXPLOSION INFORMATION (cont.)

**HAZARD /HIE AND EXPLOSION DATA:** Container may burst in heat of fire. Mists or sprays may be flammable at temperatures below flash point. Vapors may accumulate in confined spaces (e.g., pits, sumps, sewers) and inadequately ventilated areas.

## SECTION V-HEALTH HAZARD DATA

**HAZARD ROUTE OF ENTRY:** Skin contact.

**SIGNS AND SYMPTOMS:** If taken internally, aspiration of liquid product can cause chemical pneumonitis.

**FIRST AID PRECAUTIONS:** If product is swallowed, do not induce vomiting. Seek medical aid at once.

**MEDICAL CONDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE:** None known to S.C. Johnson Wax.

## SECTION VI-REACTIVITY DATA

**STABILITY:** Stable

**STABILITY-CONDITIONS TO AVOID:** None known

**INCOMPATIBILITY:** None known

**HAZARDOUS DECOMPOSITION PRODUCTS:** When exposed to fire, produces normal products of combustion.

**HAZARDOUS POLYMERIZATION:** Will not occur.

**HAZARDOUS POLYMERIZATION-CONDITIONS TO AVOID:** None known

## SECTION VII-SPILL OR LEAK PROCEDURES

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Eliminate all ignition sources. Do not let spilled or leaking material enter watercourse. Contains Amyl acetate. May be toxic to aquatic life. Absorb with oil-dri or similar inert material. Sweep or scrape up and containerize.

**WASTE DISPOSAL INFORMATION:** Recycle empty aerosol can to nearest steel recycling center. Use up package or give to someone who can.

## SECTION VIII-SPECIAL PROTECTION INFORMATION

**RESPIRATORY PROTECTION:** No special requirements under normal use conditions.

**VENTILATION:** General room ventilation adequate.

**PROTECTIVE CLOTHES:** No special requirements under normal use conditions.

**EYE PROTECTION:** No special requirements under normal use conditions.

**OTHER PROTECTIVE MEASURES:** Use good personal hygiene practices.

## SECTION IX-SPECIAL PRECAUTIONS

**PRECAUTIONARY LABELING:** DANGER: Keep out of reach of children. Harmful or fatal if swallowed. Flammable. Contents under pressure. Contains mineral seal oil. If swallowed, do not induce vomiting. Call a physician immediately. Do not store near stove or radiator or where temperature will exceed 120 F as container may burst. Do not puncture or throw in fire.

# MATERIAL SAFETY DATA SHEET

Page 3

S.C. Johnson Wax  
1525 Howe Street  
Racine, Wisconsin 53403

CONQ-R-DUST PRESSURIZED

Product Number: 14750

Serial Number: 5

## SECTION IX-SPECIAL PRECAUTIONS (cont.)

**OTHER LABELING AND STORAGE CONDITIONS:** Store in a cool, dry place with adequate ventilation. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. Do not pressurize, cut, heat, weld or expose container to flame; explosion could occur.

## SECTION X-ADDITIONAL INFORMATION

**NOTIFICATION INFORMATION:** NFPA 308 Level 2

**EPA REGISTRATION #:** NA

## SECTION XI-TRANSPORTATION INFORMATION

**DOT CLASS:** ORM-D. CONSUMER COMMODITY

**DOT #:** None

**SHIPPING NAME:** Cleaning, Scouring, or Washing Compounds, NOI, Liquid.

## SECTION XII-REGULATORY INFORMATION

**ALL** components of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory. There are no ingredients subject to the reporting requirements under California's Proposition 65.

**NA** - These ingredients are subject to the reporting requirements under the Massachusetts Hazardous Substance List.

**NJ** - These ingredients are subject to the reporting requirements under the New Jersey Right to Know Hazardous Substance List.

**PA** - These ingredients are subject to the reporting requirements under the Pennsylvania Hazardous Substance List.

Not Applicable, Not Established, Not Special Requirement, Not Determined  
The information herein is given in good faith. No warranty expressed or implied is made. Any use of these data and information must be determined by the user to be in accordance with applicable federal, state, and local laws and regulations. The information contained in this form is confidential and is submitted solely for your organization's internal use.  
E-106 (Rev 5 - 10/90)