## **Material Safety Data Sheet**

0776-06, 0779 Non-Flammable Construction Adhesive – General Purpose – Solvent-Free

MSDS No. 0076 Rev. 4

Emergency Phone No. 800-535-5053 - INFOTRAC

SECTION 1 – PRODUCT NAME & MANUFACTURER INFORMATION								
PRODUCT NAME	Non-Flammable Construction Adhesive – VOC Compliant – 9 oz 28 oz Cartridge							
MANUFACTURER'S N TELEPHONE NUMBE		&						
STREET ADDRESS	4175 Webb Street							
CITY / STATE / ZIP	Pryor, Oklahoma 74361							
SECTIO	ON 2 – COMPOSITI	ON / HAZARDOUS I	INGREDIENTS	%	TLV	PEL	UNITS	
PRODUCT CONSISTS	OF:							
Calcium Carb	onate ** (1317-65-3)			< 50	10	15	mg/m3	
Acrylic Emulsion (mixture)				< 35	NE	NE		
Benzoate Ester (proprietary)				< 5	NE	NE		
Ammonium Hydroxide (7664-41-7)				< 0.25	25	50	ppm	
Non-hazardous ingredients*					NA	NA		
*Unlisted ingredients are not considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200). **Inhalation not likely due to products physical state.  Calculated VOC: < 0.5%/wt (< 7 g/L). CARB Compliance: Yes. Prop 65 Ingredients: Yes (See Section 16)								
	S	ECTION 3 – HAZAR	DS IDENTIFICATION	ON				
PRIMARY ROUTE(S) OF ENTRY	Skin Contact	Skin Absorption	Eye Contact			estion		
EMERGENCY OVERVIEW	Off-white colored paste product. Harmful if swallowed.							
EFFECTS OF OVEREXPOSURE	May cause eye, skin, nose, throat & respiratory tract irritation.							
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE	None known.							
		SECTION 4 – FIRS	T AID MEASURES					
SKIN CONTACT	Wash w/ soap & water for @ least 15 minutes. Get medical attention if symptoms persist. Remove & wash contaminated clothing.							
EYE CONTACT	Immediately flush w/ large quantities of water for @ least 15 minutes until irritation subsides. Get medical attention.							
INHALATION	Remove to fresh air. If breathing difficult, leave area to obtain fresh air. If breathing remains difficult, get medical attention.							
INGESTION	INGESTION  DO NOT INDUCE VOMITING. Get immediate medical attention.							

SECTION 5 – FIRE FIGHTING MEASURES						
FLAMMABLE Yes No						
EXTINGUISHING MEDIA  Carbon Dioxide, Dry Chemical, Foam, Water Fog MEDIA						
FLASHPOINT (°F) & >200F (Closed Cup)  WETHOD  UPPER EXPLOSIVE LIMIT (% BY VOLUME)						
LOWER EXPLOSIVE LIMIT NE AUTOIGNITION NE (% BY VOLUME) TEMPERTURE (°F)						
UNUSUAL FIRE & EXPLOSION None known. HAZARDS						
SPECIAL Wear self-contained breathing apparatus pressure demand (NIOSH approved or equivalent) & full protective gear. Use water spray to FIREFIGHTING PROCEDURES  Wear self-contained breathing apparatus pressure demand (NIOSH approved or equivalent) & full protective gear. Use water spray to cool exposed surfaces.						
SECTION 6 – ACCIDENTAL RELEASE MEASURES						
PROCEDURES Wear proper protective equipment (Section 8). Use absorbent material or scrape up dried material & place in approved container.						
SECTION 7 – HANDLING & STORAGE						
HANDLING PROCEDURES & EQUIPMENT  Keep out of reach of children & pets. Do not take internally. Do not breathe vapors. Use only w/ adequate ventilation. Wash thoroughly after handling. Avoid contact w/ eyes, skin & clothing. Open windows & doors to ensure cross-ventilation & fresh air during application & curing.						
STORAGE REQUIREMENTS  Close container after each use. Store containers away from excessive heat & freezing. Do not store @ temperatures above 120F. Store away from caustics & oxidizers.	re					
SECTION 8 – EXPOSURE CONTROL / PERSONAL PROTECTION						
RESPIRATORY In case of insufficient ventilation, wear suitable respiratory equipment. A NIOSH-approved air purifying respirator w/ organic vapor cartridge may be necessary under circumstances where concentrations are expected to exceed exposure limits.						
EYEWEAR Goggles or safety glasses w/ side shields.						
CLOTHING / GLOVES Rubber gloves. Other protective equipment not required under normal use.						
HYGENIC PRACTICES  Remove & wash contaminated clothing before re-use. Wash hands before breaks & @ end of workday.						
SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES						
PHYSICAL STATE Viscous paste ODOR & Mild acrylic/ammonia. Smooth paste.  APPEARANCE						
SPECIFIC GRAVITY Approximately 1.0 to 1.50 VAPOR DENSITY Heavier than air (AIR=1)						
EVAPORATION RATE Slower than n-Butyl Acetate BOILING RANGE (°F) 210 to 220F						
pH Approximately 7 to 10 SOLUBILITY IN Slight, before cure. WATER						
VAPOR PRESSURE (MM NE %/WT VOLATILE (TNV) Approximately 25 to 30% (TNV)						
SECTION 10 – STABILITY AND REACTIVITY						
STABILITY Yes No Stable under normal conditions.						
INCOMPATABILITY Yes No Incompatible w/ strong bases & oxidizing agents.						
CONDITIONS TO AVOID Excessive heat & freezing.						
HAZARDOUS POLYMERIZATION/HAZARDOUS DECOMPOSITION PRODUCTS Hazardous polymerization will not occur under normal conditions. Normal decomposition products, ie: COx, NOx.						

S	ECTION 11 – TOXICOLOGICAL IN	FORMATION / CARCINOGENICITY					
ACGIH	Small amount of Silica, crystalline present in Calcium Carbonate & trace residual Formaldehyde present in base emulsion are suspected human carcinogens.						
OSHA	Trace residual Formaldehyde present in base emulsion viewed as a possible cancer hazard.						
IARC	C Trace residual Formaldehyde: Human carcinogen.						
NTP	Silica, crystalline, present in small amount in Calcium Carbonate Filler: Known carcinogen. Trace residual Formaldehyde: Anti						
DATA WITH POSSIBLE RELEVANCE TO HUMANS	Product contains trace amounts of residual Formaldehyde. OSHA & NTP identify Formaldehyde as a potential carcinogen. IARC identifies Formaldehyde as a human carcinogen. Formaldehyde has been shown to cause mutations in a variety of in-vitro test systems, w/ human significance unknown. Rats have shown carcinogenic effects in respiratory system. Risk should be minimal when used w/ adequate ventilation. Maintain adequate ventilation to prevent exposure above OSHA exposure limits.						
SECTION 12 – ECOLOGICAL INFORMATION							
AQUATIC TOXICITY	Not known or expected under normal use.						
SECTION 13 – DISPOSAL CONSIDERATIONS							
WASTE DISPOSAL	Dispose of material in accordance w/ Federal, State & Loca	al regulations.					
EPA WASTE CODE IF DISCARDED (40CFR Sec.261)	None.						
SECTION 14 – TRANSPORT INFORMATION							
SPECIAL SHIPPING INFORMATION							
SECTION 15 – REGULATORY INFORMATION							
CERCLA – SARA Imr HAZARD CATEGORY	nediate health hazard; chronic health hazard.	U.S. STATE See Section 16. REGS					
SARA 313 Nor	ne.	TSCA All ingredients either on TSCA Inventory or exempt.					
SECTION 16 – OTHER INFORMATION / SPECIAL PRECAUTIONS / LEGEND							
(57-55-6) <u>Pennsylvania l</u> WARNING: This product	Right-to-Know (Non-Haz @ >3%): Water (7732-18-5). HMIS contains chemicals known to the State of California to cause of	Emulsion (mixture), Benzoate Ester (proprietary), Water (7732-18-5), Propylene Glycol <u>Ratings</u> : Health: 1, Flammability: 0, Reactivity: 0, Personal Protection: B. cancer, birth defects or other reproductive harm. (Trace Residual Formaldehyde (50-00-m carbonate filler.) INTERNATIONAL EMERGENCY NUMBER: 352-323-3500 -					

<u>LEGEND</u>: NA – Not Applicable, NE – Not Established, UN – Unavailable, VOC – Volatile Organic Compound, PEL – Permissible Exposure Limit, TLV – Threshold Limit Value, STEL – Short Term Exposure Limit, MSDS – Material Safety Data Sheet, ACGIH – American Conference of Governmental Industrial Hygienists, SARA – Superfund Amendments & Reauthorization Act of 1986, OSHA – Occupational Safety & Health Administration, HMIS – Hazardous Materials Identification System, NTP – National Toxicology Program, CEIL – Ceiling Exposure Limit, CASRN (CAS Number) – Chemical Abstracts Service Registry Number, TSCA – Toxic Substances Control Act

Reviewed By: Larry G. Brandon VP Technology & General Manager March 7, 2012

NAME TITLE DATE

The information contained herein has been developed based upon currently available scientific data. New information may be developed from time to time which may render the conclusions of this report obsolete. Therefore, no warranty is extended as to the applicability of this information to the user's intended purpose or for the consequences of its use or misuse.