

Spartan Chemical Company, Inc. Material Safety Data Sheet

SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label):

STEP DOWN

Product Number: 0065

Product Division:

Janitorial

Spartan Chemical Company, Inc.

1110 Spartan Drive Maumee OH 43537 Product/Technical Information: 1-(800)-537-8990

Medical Emergency: 1-(888)-314-6171 (24 hours)

Chemical Leak/Spill Emergency: CHEMTREC 1-(800) 424-9300 (24 hours)

Shipping Description: UN 1760, Corrosive liquids, n.o.s., (contains sodium hydroxide, ethanolamine), 8, II

NFPA Ratings:	HMIS Ratings:
Health: 3 - Serious	Health: *3 - Serious; Chronic Hazard
Fire: 0 - Minimal	Fire: 0 - Minimal
Reactivity: 0 - Minimal	Reactivity: 0 - Minimal
- 5	Pers. Prot. Equip.: See Section VIII

SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

				Table Z-1-A		
Chemical Name(s)	%Wt	CAS Registry No.	TWA mg/m³	STEL mg/m³	CEILING mg/m³	NTP, IARC or OSHA Carcinogen
Benzyl alcohol	10-15	100-51-6	44 (AIHA WEEL)	Not Established	Not Established	No
Monoethanolamine	5-10	141-43-5	6	15 (ACGIH)	Not Established	No
Sodium xylene sulfonate	1-5	1300-72-7	Not Established	Not Established	Not Established	No
Dicarboxylic fatty acid	1-5	53980-88-4	Not Established	Not Established	Not Established	No
Sodium hydroxide	1-5	1310-73-2	2 (OSHA)	Not Established	2 (ACGIH)	No
Alcohol ethoxylate	1-5	68439-46-3	Not Established	Not Established	Not Established	No

SECTION III: PHYSICAL DATA

Boiling Point: 212 °F	Vapor Pressure: Unknown
Vapor Density (AIR = 1): Unknown	Solubility in Water: Complete
pH: 13.5-14.0	Specific Gravity (H ₂ O=1): 1.052
Evaporation Rate (but.ace.=1): <1	Percent Solid by Weight: 30-40 %
Physical State: Liquid	
Appearance & Odor: Clear liquid. Mild odor.	

SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

> 212°F	Method Used: ASTM-D56	
Not Established	Flame Extension: N/A	
Carbon dioxide, dry chemical, synth	netic foam or water.	
	ed breathing apparatus and protective clothing. Cool fire-exposed	
Combustion products are toxic.		
	Not Established Carbon dioxide, dry chemical, synth Wear NIOSH approved self-contain	

Threshold Limit Value:		Primary Routes of Entry: Inhalation, Skin Contact, Eyes & Ora	
Effects of Overexposure- Conditions to Avoid:	Corroller: Causes severe eye damage: Symptoms include chemical burns, pain, redness, swelling of the conjunctiva, tissue destruction and possible permanent corneal damage. Causes severe skin damage: Symptoms include chemical burns, pain, redness and tissue destruction. Harmful contact may not cause immediate pain. Harmful or fatal if swallowed: Causes damage or chemical burns to esophagus and mucous membranes with symptoms of pain, nausea, vomiting and diarrhea. Harmful if inhaled: Breathing product vapor or mist may cause irritation or damage of the respiratory tract, with symptoms of nasal discomfort and coughing. Harmful if absorbed through skin. Contains benzyl alcohol which may cause headache, dizziness, nausea and drowsiness. Contains monoethanolamine which may cause liver and kidney damage with repeated exposure. DO NOT GET IN EYES, ON SKIN OR CLOTHING. AVOID BREATHING PRODUCT VAPOR OR MIST. DO NOT SWALLOW. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER		
Conditions Aggravated by Use:	 Use of this product may aggravate preexisting skin; eye and respiratory disorders including asthma and dermatitis. 		
mergency & First Aid Procedures:			
	attention.	of water for at least 15 minutes. Remove contact lenses. Get medical	
Skin:	Remove contaminated clothing and attention. Wash contaminated clot	shoes. Flush skin with water for at least 15 minutes. Get medical hing before reuse. Destroy contaminated shoes.	
Ingestion:	Call a poison control center or doctor immediately for treatment advice. Do not induce vomiting. Drink one or two glasses of water to dilute product. Do not give anything by mouth to an unconscious person.		
Inhalation:	In case of respiratory irritation or di	zziness; move person to fresh air. If not breathing; give artificial give oxygen. Get medical attention if irritation persists.	

Incompatible Materials: Strong acids and oxidizing agents		
Hazardous Polymerization: Will Not Occur		

SECTION VII: SPILL OR LEAK PROCEDURES

Steps to be Taken in Case

Material is Released or Spilled: Contain large spills and transfer the material to appropriate containers for reclamation or disposal. Absorb remaining material or small spills with an inert material and dispose of in accordance with federal, state and local regulations. Keep spill out of storm sewers and waterways.

Waste Disposal Method: Assure conformance with federal, state and local regulations.

SECTION VIII: SPECIAL PROTECTION INFORMATION

Respiratory Protection: Not expected to be required with intended use. However, if If exposure limits (see Section II) are exceeded or respiratory irritation occurs, use of a NIOSH approved respirator suitable for the use-conditions and chemicals in Section II should be considered. (N95 with organic vapor cartridge is recommended) Ventilation: Provide good general ventilation. Local exhaust ventilation may be necessary for some operations. Protective Gloves(Specify Type): Solvent/alkali resistant gloves such as neoprene, nitrile or natural rubber. Eye Protection(Specify Type): Splash goggles are recommended to prevent eye contact. Other Protective Equipment: Solvent /alkali resistant boots are recommended. Use of impervious apron, face shield and other protective equipment should be considered in order to prevent or minimize contact with this product. Eye wash stations and washing facilities should be readily accessible. See 29 CFR 1910.132-138.

SECTION IX: SPECIAL PRECAUTIONS

Precautions; Handling & Storing: Keep container tightly closed. Do not freeze. Do not store above 120°F. Do not mix with other chemicals. Other Precautions: Keep out of reach of children.

© SCC 06/01/2013

Name:

Ronald T. Cook

Title:

Manager, Regulatory Affairs

ral

STEP DOWN

Effective Date: 06/01/2013

Supercedes:

10/17/2012

Ref: 29 CFR 1910.1200 (OSHA)

Changes:

Formula Revision

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.