SLICK 50 INC -- SLICK 50 ONE LUBE, 436/437 -- 9150-00N077020 _____ MSDS Safety Information _____ FSC: 9150 MSDS Date: 01/15/1995 MSDS Num: CDNGC LIIN: 00N077020 Tech Review: 03/05/1997 Product ID: SLICK 50 ONE LUBE, 436/437 Responsible Party Cage: 10948 Name: SLICK 50 INC Address: 1187 BRITTMOORE RD City: HOUSTON TX 77043 US Info Phone Number: 800-444-7542 Emergency Phone Number: 800-255-3924 Proprietary Ind: Y Review Ind: N _____ Contractor Summary _____ Cage: 10948 Name: SLICK 50 INC Address: 1187 BRITTMOORE RD City: HOUSTON TX 77043 US Phone: 800-444-7542 Cage: SLXCK Name: SLICK 50 INC Box: UNKNOW City: UNKNOWN NK 00000 Country: NK Ingredients ______ Name: *** PROPRIETARY *** _____ _____ Health Hazards Data ______ LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Route Of Entry Inds - Inhalation: YES Skin: YES Ingestion: YES Carcinogenicity Inds - NTP: NO IARC: NO OSHA: NO Effects of Exposure: ACUTE: INHAL: VAP PRESS IS LOW. VAP INHAL UNDER AMBIENT CNDTNS IS NOT EXPECTED. SKIN: MAY DRY SKIN. PRLNG CONT MAY CAUSE IRRIT/DERM. EYES: SLIGHT IRRIT. INGEST: NOT A LIKELY RTE OF EXPOS. DO NOT INDUC E VOMIT. CHRONIC: PRLNG/RPTD SKIN CONT MAY CAUSE SKIN IRRIT. NO OTHER CHRONIC EXPOS EFTS EXPECTED. Explanation Of Carcinogenicity: NOT RELEVANT. Signs And Symptions Of Overexposure: SEE HEALTH HAZARDS. Medical Cond Aggravated By Exposure: NONE RECOGNIZED. First Aid: INHALATION: IF EXPOSED TO VAPOR FROM PRODUCT AND OVERCOME, REMOVE FROM EXPOSURE AND CALL MD. SKIN: REMOVE CONTAMINATED CLOTHING. WASH SKIN WITH SOAP AND WATER. EYES: FLUSH FOR AT LEAST 15 MINUTES WITH WATER OR UNTIL IRRITATION SUBSIDES. IFIRRITATION PERSISTS CALL MD.

INGESTION: IF INGESTED DO NOT INDUCE VOMITING. CALL MD. _____ Handling and Disposal _____ Spill Release Procedures: RECOVER FREE PROD. ADD SAND, EARTH/OTHER SUITABLE ABSORB MATL TO SPILL AREA. KEEP PROD OUT OF SEWERS & WATERCOURSES BY DIKING & IMPOUNDING. SML SPILL: SAME. LGE SPILL: SAME. IF PROD REACHES WATERCOURS ES, SEWERS/EXTENSIVE LAND AREA, ASSURE (SUP DAT) Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER. Waste Disposal Methods: DISPOSE OF IN CONFORMITY WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS AS APPLICABLE. Handling And Storage Precautions: STORE BELOW 150F. KEEP AWAY FROM HIGH HEAT OR FLAMES. Other Precautions: DO NOT STORE IN PROXIMITY OF STRONG OXIDIZERS. AVOID CONTACT WITH OXYGEN, CALCIUM HYPOCHLORITE, SODIUM HYPOCHLORITE, CHLORINE, ETC. _____ Fire and Explosion Hazard Information _____ Flash Point Method: PMCC Flash Point Text: 230F,110C Extinguishing Media: FOAM, CARBON DIOXIDE, DRY CHEMICAL. Fire Fighting Procedures: WEAR NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT (FP N). Unusual Fire/Explosion Hazard: USE CAUTION WHEN HANDLING AROUND HEAT, SPARKS, PILOT LIGHTS, STATIC ELECTRICITY OR OPEN FLAME. _____ Control Measures _____ Respiratory Protection: VENT TO KEEP EXPOSURES BELOW TLV'S. USE NIOSH APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN (FP N). Ventilation: USE LOCAL EXHAUST. Protective Gloves: CHEMICAL RESISTANT GLOVES. Eye Protection: ANSI APPRVD CHEM WORKERS GOGGLES (FP N). Other Protective Equipment: NONE REQUIRED WHEN USED AS INTENDED. EMERGENCY EYEWASH AND DELUGE SHOWER MEETING ANSI DESIGN CRITERIA (FP N). Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER. Supplemental Safety and Health: SPILL PROC: CONFORMITY W/APPLIC GOVERNMENTAL REGULATIONS. _____ Physical/Chemical Properties _____ B.P. Text: 640F,338C Vapor Density: >1.0 Spec Gravity: 0.553 (H*20=1) Solubility in Water: NEGLIGIBLE Appearance and Odor: HAZY STRAW COLORED LIQUID Percent Volatiles by Volume: NEGLIG _____ Reactivity Data _____ Stability Indicator: YES Stability Condition To Avoid: HIGH TEMPERATURES. Materials To Avoid: STRONG OXIDIZING AGENTS. Hazardous Decomposition Products: CARBON MONOXIDE, ALDEHYDES. Hazardous Polymerization Indicator: NO Conditions To Avoid Polymerization: NOT RELEVANT. _____

Toxicological Information _____ _____ Ecological Information _____ _____ MSDS Transport Information _____ _____ Regulatory Information _____ _____ Other Information _____ ______ HAZCOM Label _____ Product ID: SLICK 50 ONE LUBE, 436/437 Cage: 10948 Company Name: SLICK 50 INC Street: 1187 BRITTMOORE RD City: HOUSTON TX Zipcode: 77043 US Health Emergency Phone: 800-255-3924 Date Of Label Review: 03/05/1997 Label Date: 03/05/1997 Chronic Hazard IND: Y Eye Protection IND: YES Skin Protection IND: YES Signal Word: WARNING Respiratory Protection IND: YES Health Hazard: Slight Contact Hazard: Slight Fire Hazard: Moderate Reactivity Hazard: None Hazard And Precautions: COMBUSTIBLE. ACUTE: INHALATION: VAPOR PRESSURE IS LOW. VAPOR INHALATION UNDER AMBIENT CONDITIONS IS NOT EXPECTED. SKIN: MAY DRY SKIN. PROLONGED CONTACT MAY CAUSE IRRITATION OR DERMATITIS. EYES: SLIGHT IRRITATION. INGESTION: NOT A LIKELY ROUTE OF EXPOSURE. CHRONIC: PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE SKIN IRRITATION. NO OTHER CHRONIC EXPOSURE EFFECTS EXPECTED. _____ Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.