

Office Products North America Markers and Adhesives 20955 Pathfinder Road Diamond Bar, CA 91765 Phone: 615-456-8219 (8 am-5 pm CDT M-F)

Avery Dennison Product: Stamp Pad Ink

SECTION						
Material Name	:	CAS #:	OSHA I	PEL (ppm):	ACGIH TLV (ppm):	
Ethylene Glycol		107-21-1	50		50	
All of the chemicals listed above are in compliance with OSHA, CFR, 1910.1200. A finished stamp pad contains a substantially lower percentage by weight of each chemical and has the ink held within an absorbent material.						

SECTION III PHYSICAL DATA

SECTION II

Boiling Point: 365°F Specific Gravity: 1.04 @ 20°C Vapor Pressure (mmHg): 0.22 @ 20°C Vapor Density (Air=1): N/AP Melting Point: N/AP Appearance: Liquid, colored Odor: Mild odor Water Solubility: Complete Evaporation Rate (Butyl Acetate=1): < 0.01

SECTION IV FIRE AND EXPLOSION HAZARD DATA

 Flash Point: 225°F (method used - PMCC)
 Flammable Limits: N/AP

 Extinguishing Media: Foam, carbon dioxide, dry chemical
 Unusual Hazards: None

 Fire Fighting Procedure: Wear self-contained breathing apparatus, use water spray to cool nearby containers

HAZARDOUS INGREDIENT/IDENTITY INFORMATION

SECTION V REACTIVITY DATA

 Stability: Yes
 Conditions to Avoid: N/AP

 Incompatibility: Strong oxidizing agents
 Hazardous Polymerization: Will not occur

 Hazardous Decomposition: May form toxic materials, carbon dioxide or carbon monoxide

SECTION VI HEALTH HAZARD DATA

Symptoms of Overexposure for each Potential Route of Exposure -

Inhaled: No symptoms expected Eye Contact: May cause eye irritation Absorbed through Skin: No evidence of harmful effects Ingestion: May cause abdominal discomfort or pain, nausea, vomiting, dizziness, drowsiness, central nervous system effects Health Effects or Risks from Exposure -Chronic - No Medical Conditions Aggravated by Exposure: Carcinogenic: No This product contains materials that are listed on the following lists: NTP: No IARC: No OSHA: No S.A.R.A. Information: This product is not reportable under SARA Title III, Section 313 Toxic Information: Non-toxic per ASTM D-4236 **Emergency First Aid Procedures -**Eye Contact: Flush with large amounts of water, if eye irritation occurs, get medical attention Skin Contact: Thoroughly wash with soap and water Inhaled: Remove to fresh air, obtain medical attention if symptoms persist Ingestion: If conscious, give two glasses of water, induce vomiting, and obtain medical attention without delay

SECTION VII PRECAUTIONS FOR SAFE HANDLING AND USE

Spill or Leak Procedures: Absorb liquid on paper or other absorbent material, flush with water Waste Disposal: Dispose of in accordance with local, state, federal regulations Storage: N/AP

SECTION VIII CONTROL MEASURES

Work Practices: Observe ordinary measures of personal hygiene

To the best of our knowledge this information is accurate; however, we do not, and cannot, warrant or guarantee its accuracy and cannot be liable for any damages, consequential or actual which might result from any reliance therein. This MSDS was prepared to comply with the OSHA Hazard Communication Standard (29 CFR 1910.1200).