


MATERIAL SAFETY DATA SHEET

Share Corporation
P.O. Box 245013
Milwaukee, WI 53224



GENERAL INFORMATION NUMBER: 414-355-4000
EMERGENCY TELEPHONE NUMBER: (800) 776-7192
CHEMTREC: (800) 424-9300

REVISION DATE: February 16, 2011
DATE OF ISSUE: February 16, 2011

I - Product Identification

Rubber In A Can

PRODUCT CODE: 8002

CHEMICAL FORMULATION: Pressurized rubber coating.

NFPA HAZARD IDENTIFICATION SYSTEM: HEALTH: 2

FLAMMABILITY: 3

REACTIVITY: 0

HAZARD RATING: 4 - Extreme; 3 - High; 2 - Moderate; 1 - Slight; 0 - Insignificant

II - Hazardous Ingredients

Values reported as TWA unless noted.

SUBSTANCE	APPROX %	OSHA PEL	ACGIH TLV	EPA 40 CFR:			CAS #
				302	355	372	
Calcium carbonate	30.0-40.0	15 mg/m ³	10 mg/m ³	N	N	N	1317-65-3
Toluene	10.0-20.0	200 ppm	20 ppm	Y	N	Y	108-88-3
Methyl acetate	10.0-20.0	200 ppm	200 ppm	N	N	N	79-20-9
Propane/Isobutane/n-Butane	1.0-10.0	800 ppm	1000 ppm	N	N	N	68476-86-8
2-Propanone	1.0-10.0	1000 ppm	500 ppm	Y	N	N	67-64-1
1,2-Benzenedicarboxylic, dibutyl ester	1.0-10.0	5 mg/m ³	5 mg/m ³	Y	N	Y	84-74-2

Key: PEL: Permissible Exposure Limit TLV: Threshold Limit Value C: Ceiling level STEL: Short Term Exposure Limit
N/A: Not Applicable N/D: Not Determined N/E: Not Established Y: Yes N: No
302: CERCLA List of Hazardous Substances and Reportable Quantities (40 CFR 302.4).
355: SARA TITLE III / List of Extremely Hazardous Substances for Emergency Planning and Notification (40 CFR 355).
372: SARA TITLE III / List of Toxic Chemicals subject to Release Reporting (Community Right to Know) (40 CFR 372).

III - Physical Data

BOILING POINT (°F): -23 to 645

SPECIFIC GRAVITY (WATER = 1): 1.0024

VAPOR PRESSURE (psig): N/D

VOC CONTENT (% by weight): 37.32

VAPOR DENSITY (AIR = 1): > 1.0

EVAPORATION RATE (Butyl Acetate = 1): < 1.0

SOLUBILITY IN WATER: Negligible

pH: N/A

APPEARANCE AND ODOR: Black liquid; solvent odor.

IV - Fire and Explosion Hazard Data

FLASH POINT (°F): -156

(TEST METHOD): Closed Cup

NFPA 30B Rating: 2

FLAMMABLE LIMITS IN AIR (VOLUME %) UPPER: 16.0 LOWER: 1.2

FLAME EXTENSION: N/D

EXTINGUISHING MEDIA: Foam, carbon dioxide, dry chemical and water fog.

SPECIAL FIRE FIGHTING PROCEDURES: Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Water runoff can cause environmental damage. Dike and collect water used to fight fire. Keep containers and surroundings cool with water spray. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

UNUSUAL FIRE AND EXPLOSION HAZARD: Vapors may form explosive mixture with air. Vapors can travel to a source of ignition and flash back. Flammable Liquid. Can release vapors that form explosive mixtures at temperatures at or above the flashpoint. "Empty" I containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Contents under pressure. Containers may explode if exposed to high temperatures.

V - Reactivity Data

STABILITY: Stable

INCOMPATIBILITY: Oxygen and strong oxidizing agents such as chlorates, nitrates, peroxides, etc.

CONDITIONS TO AVOID: All sources of ignition, welding arcs, and open flames and high temperatures. Keep product away from temperatures in excess of 120°F (49°C). Do not crush, puncture or incinerate container. Do not expose to direct sunlight or store where temperatures could exceed 120°F.

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may produce oxides of carbon.

HAZARDOUS POLYMERIZATION: Will not occur.

VI - Health Hazard Data

ROUTES OF ENTRY INHALATION: X **EYE CONTACT:** X **SKIN CONTACT:** X **INGESTION:** X

INGREDIENTS THAT ARE CONSIDERED BY OSHA, NTP, IARC TO BE SUSPECTED HUMAN CARCINOGENS: None

EFFECTS OF OVEREXPOSURE

IF IN EYES: Causes moderate to severe eye irritation, redness, and pain

IF ON SKIN: Causes skin irritation. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash). May be absorbed through the skin in harmful amounts and may produce systemic toxicity.

IF SWALLOWED: Not considered to be a hazard encountered in normal industrial use. This material may be harmful or fatal if swallowed. Irritating to mouth, throat and stomach. Aspiration hazard. Depression of the central nervous system can occur.

IF INHALED: Prolonged inhalation may be harmful. Inhaling large quantities of mist or vapors may cause some irritation to nose, throat, lungs. High doses may cause central nervous system depression. May cause damage liver, lungs, and kidneys.

EMERGENCY AND FIRST AID PROCEDURES

IF IN EYES: Flush under eyes and eyelids with plenty of cool water for at least 15 minutes. If irritation persists, obtain medical attention.

IF ON SKIN: Remove contaminated clothing. Wash with soap and water. If irritation persists, obtain medical attention.

IF SWALLOWED: Do not induce vomiting. Obtain medical attention.

IF INHALED: Remove person to fresh air and provide oxygen if breathing is difficult. If breathing has stopped, administer artificial respiration. Obtain medical attention.

VII - Spill or Leak Protection

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition and ventilate area. Soak up spilled material with inert absorbent material and place in a properly labeled closed container.

WASTE DISPOSAL METHOD: Consult local environmental authorities. Dispose of empty cans in non-incinerated trash only.

VIII - Special Protection Information

RESPIRATORY PROTECTION: None required if good ventilation is maintained. If recommended exposure limits are exceeded wear a NIOSH approved respirator, following manufacturer's recommendations.

VENTILATION

LOCAL: Recommended

MECHANICAL: Not required

PROTECTIVE GLOVES: Chemical resistant

EYE PROTECTION: Safety glasses.

OTHER PROTECTIVE EQUIPMENT: Protective clothing.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in a cool, dry place away from heat or open flame. Keep container tightly closed when not in use.

OTHER PRECAUTIONS: Keep out of reach of children. Do not puncture or incinerate cans.

IX - Transportation Information

DOT ID NUMBER: None

DOT PROPER SHIPPING NAME: Consumer Commodity

DOT CLASS: ORM-D

DOT PACKING GROUP: None

The shipping information listed above applies only to non-bulk (< 119 gallons) containers of this product. This product may have more than one proper shipping name depending on packaging, product properties, & mode of shipment. If any alteration of packaging, product, or mode of transportation is further intended, different shipping names and labeling may apply.

REVISION DATE: February 16, 2011

Preparers Technical Dept.

DATE OF ISSUE: February 16, 2011

This information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Share Corporation assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material such vendees or users assume all risks associated with the use of this material.