

=====
Section 1 -- PRODUCT AND COMPANY IDENTIFICATION
=====

PRODUCT NAME	HMIS CODES
RectorSeal Tru-Blu	Health 1
	Flammability 2
	Reactivity 0
PRODUCT CODES	PPI B
31300, 31431, 31551, 31552, 31631, 31780, 31782, 31785	
CHEMICAL FAMILY:	
Organic	
USE	
Pipe Thread Sealant	
MANUFACTURER'S NAME	EMERGENCY TELEPHONE NO.
The RectorSeal Corporation	Chemtrec 24 Hours
2601 Spenwick Drive	(800)424-9300 USA
Houston, Texas 77055 USA	(703)527-3887 International
DATE OF VALIDATION	TECHNICAL SERVICE TELEPHONE NO.
July 9, 2012	(800)231-3345 or (713)263-8001
DATE OF PREPARATION	
July 9, 2012	

=====
Section 2 -- HAZARDS IDENTIFICATION
=====

EMERGENCY OVERVIEW
OSHA Hazards
Combustable
TARGET ORGANS
Not Classified
GHS CLASSIFICATION
PHYSICAL HAZARDS
Combustable liquid (Category 4)
HEALTH HAZARDS
Acute Toxicity:
Oral: Not Classified
Dermal: Not Classified
Inhalation: Not Classified
Skin Corrosion/Irritation: Not Classified
Serious Eye Damage/Eye Irritation: Not Classified
Skin Sensitization: Not Classified
Respiratory Sensitization: Not Classified
Germ Cell Mutagenicity: Not Classified
Carcinogenicity: See Section 11
Reproductive Toxicology: Not Classified
Target Organ Systemic Toxicity - Single Exposure: Not Classified
Target Organ Systemic Toxicity - Repeated Exposure: Not Classified
Aspiration Toxicity: Not Classified

GHS Label elements, including precautionary statements
Pictogram: Harmful / Irritant
Signal Word: Warning
Hazard Statements
H303 - May be harmful if swallowed.

H313 - May be harmful in contact with skin.
H335 + H336 - May cause respiratory irritation, and drowsiness or dizziness.
Precautionary Statements
P102 - Keep out of reach of children.
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking
P240 - Ground/Bond container and receiving equipment
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
P262 - Do not get in eyes, on skin, or on clothing.
P264 - Wash hands thoroughly after handling.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
P362 - Take off contaminated clothing and wash before reuse.
EUH066 - Repeated exposure may cause skin dryness or cracking
Precautionary Statements - EU No. 1272/2008

SUMMARY OF ACUTE HAZARDS

Irritation to eyes, nose and throat; drowsiness, narcosis, tremors and other CNS effects at high concentration.

ROUTE OF EXPOSURE, SIGNS AND SYMPTOMS

INHALATION

Nasal and respiratory irritation, dizziness, narcosis, headache, nausea, CNS depression and unconsciousness.

EYE CONTACT

Watering, blurred vision, inflammation and irritation which can result in corneal injury.

SKIN CONTACT

Irritation, dermatitis.

INGESTION

Nausea, vomiting; CNS depression; irritation of gastrointestinal tract, liver and peritoneal wall; lung congestion.

SUMMARY OF CHRONIC HAZARDS

Skin irritation and dermatitis. Possible liver and kidney damage.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Individuals with pre-existing or chronic diseases of the eyes, skin, respiratory system, cardiovascular system, gastrointestinal system, liver or kidneys may have increased susceptibility to excessive exposures.

Section 3 -- COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT: Diacetone Alcohol
PERCENTAGE BY WEIGHT: 20-30
CAS NUMBER: 123-42-2
EC# : 204-626-7

Section 4 -- FIRST AID MEASURES

If INHALED:	If overcome by exposure, remove victim to fresh air immediately. Give oxygen or artificial respiration as needed. Obtain emergency medical attention. Prompt action
	is essential.
If on SKIN:	Wash with soap and water. If irritation occurs, seek

medical attention.
If in EYES: Flush eyes with large amounts of water for 15 minutes.
Get medical attention.
If SWALLOWED: If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

Section 5 -- FIRE FIGHTING MEASURES

FLASH POINT	LEL	UEL
150 F (65 C) SETA CC	N/D	N/D

EXTINGUISHING MEDIA
Foam, dry chemical, carbon dioxide or water fog.

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus (SCBA) and other protective clothing. Hazardous decomposition products possible (see Section 10).

UNUSUAL FIRE AND EXPLOSION HAZARDS: Combustible - moderate flash point. Vapors heavier than air and may travel along the ground or to low spots at considerable distances to a source of ignition resulting in potential flashback. Burning liquid may float on water. Heat may build up pressure and rupture containers.

Section 6 -- ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Use absorbent materials to prevent footing hazard and to contain. Ventilate area with natural or explosion-proof, forced air ventilation. Avoid flushing into sewers, drains, waterways, and soil. Wear protective clothing and respiratory protection during cleanup.

Section 7 -- HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep container closed and upright when not in use. Do not store near heat, sparks, or open flames.

OTHER PRECAUTIONS: Avoid prolonged or repeated contact with skin or clothing. Empty containers may contain residues; treat as if full and observe all products precautions. Do not reuse empty containers.
KEEP OUT OF REACH OF CHILDREN.

Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION

INGREDIENT	UNITS
Diacetone Alcohol	
ACGIH TLV	50 ppm
OSHA PEL	50 ppm

RESPIRATORY PROTECTION (SPECIFY TYPE): In confined poorly ventilated areas, use NIOSH/MSHA approved air purifying or supplied air purifying or supplied air respirators.

VENTILATION - LOCAL EXHAUST: Acceptable

SPECIAL: Explosion-proof equipment.

MECHANICAL (GENERAL): Preferable

OTHER: N/A

PROTECTIVE GLOVES: Wear rubber gloves.

EYE PROTECTION: Chemical splash goggles (ANSI Z-87.1 or equivalent)

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Coveralls recommended.

WORK/HYGIENIC PRACTICES: Where use can result in skin contact, wash exposed

areas thoroughly before eating, drinking, smoking, or leaving work area.
Launder contaminated clothing before reuse.

Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: 322 F (161 C) @ 760mm Hg
SPECIFIC GRAVITY (H2O = 1): 1.38
VAPOR PRESSURE (mm Hg): 0.3 @ 68 F (20 C)
MELTING POINT: N/A
VAPOR DENSITY (AIR = 1): 1.1
EVAPORATION RATE (ETHYL ACETATE = 1): 0.14
APPEARANCE/ODOR: Blue Paste/Mild Odor
SOLUBILITY IN WATER: 23%
VOLATILE ORGANIC COMPOUNDS (VOC) Content
(Theoretical Percentage By Weight): 23% or (230 g/L)

Section 10 -- STABILITY AND REACTIVITY

STABILITY: Stable
CONDITIONS TO AVOID: Heat, sparks, open flames, and strong oxidizing.
Temperatures above 500 F (260 C).
INCOMPATIBILITY (MATERIALS TO AVOID): Gaseous oxygen, strong oxidizing
materials, molten alkali metals.
HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO2 and fragmented hydrocarbons.
HAZARDOUS POLYMERIZATION: Will not occur.

Section 11 -- TOXICOLOGY INFORMATION

CHRONIC HEALTH HAZARDS

No ingredients in this product is an IARC, NTP or OSHA Lister carcinogen.

TOXICOLOGY DATA

Ingredient Name

Diacetone Alcohol

Oral-Rat	LD50:4000 mg/kg
Inhalation-Human	TCLo: 100 ppm

Section 12 -- Ecological Information

ECOLOGICAL DATA

Ingredient Name

Diacetone Alcohol

Food Chain Concentration Potential	N/A
WATERFOWL TOXICITY	N/A
BOD	N/A
AQUATIC TOXICITY	N/A

Section 13 -- DISPOSAL CONSIDERATIONS

Waste Classification: Non-regulated solid waste

Disposal Method: Approved landfill

Waste from this product is not considered hazardous as defined under the
Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Dispose of in
accordance with Federal, State, and Local regulation regarding pollution.

Section 14 -- TRANSPORTATION INFORMATION

DOT: Non-Regulated
OCEAN (IMDG): Non-Regulated
AIR (IATA): Non-Regulated
WHMIS (CANADA): Non-Regulated

Section 15 -- REGULATORY INFORMATION

REGULATORY DATA
Ingredient Name

Diacetone Alcohol

SARA 313	N/A
TSCA Inventory	Yes
CERCLA RQ	N/A
RCRA Code	N/A

Section 16 -- OTHER INFORMATION

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). The information herein is given in good faith, but no warranty, expressed or implied is made. Consult RectorSeal for further information: (713) 263-8001