

MATERIAL SAFETY DATA SHEET

SECTION I: PRODUCT IDENTIFICATION

MANUFACTURER: MEYER LABORATORY, INC.
 ADDRESS: 2401 WEST JEFFERSON
 BLUE SPRINGS MO. 64015
 (816) 228-4433

TRADE NAME: **Cleans Off**

HEALTH 1
 FLAMMABILITY 0
 REACTIVITY 0
 PERSONAL PROTECTION B

0 - LEAST
 1 - SLIGHT
 2 - MODERATE
 3 - HIGH
 4 - EXTREME

EMERGENCY PHONE # (800) 424-9300

SECTION II: HAZARDOUS INGREDIENTS

CHEMICAL NAME /COMMON NAME	CAS NO.	TLV(SOURCE)
Butoxydiglycol	112-34-5	35 ppm (Manufacturer)
Isobutane	75-28-5	800 ppm (OSHA)
Propane	74-98-6	1000 ppm (OSHA)
Tetrasodium EDTA	64-02-8	NA
Water	7732-18-5	NA

All components of this product are on the TSCA Inventory or are exempted from TSCA Inventory requirements.

VOC Content: 7.99% w/w

SECTION III: PHYSICAL DATA

BOILING POINT (°F)(CONCENTRATE) 212°F
 PRESSURE 140 psig @ 70°F
 APPEARANCE AND ODOR. Clear colorless liquid with a lemon scent dispensed as a wet foam in an aerosol.

SPECIFIC GRAVITY (H₂O=1.0)(CONCENTRATE) 1.012 ± 0.005
 VAPOR DENSITY No Data
 SOLUBILITY IN WATER Complete
 pH (Conc) 10.4

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT None FLAMMABLE LIMITS No Data
 EXTINGUISHING MEDIA Use an extinguishing agent applicable to the fire's fuel source (i.e., dry chemical, CO₂ or foam).
 SPECIAL FIREFIGHTING PROCEDURES Do not enter confined fire-spaces without protective clothing and self-contained air supply. Use water spray to keep containers cool and vapors down. Do not allow runoff to enter sewers or public watercourses.
 UNUSUAL FIRE & EXPLOSION HAZARD Aerosol container (pressurized) may burst if heated over 120°F.

SECTION V: REACTIVITY DATA

STABILITY Stable
 HAZARDOUS DECOMPOSITION PRODUCTS Burning can produce oxides of carbon, soot and smoke.

INCOMPATIBILITY Strong acids, Strong Oxidizers, Reactive Metals (Aluminum, Magnesium).

SECTION VI: HEALTH HAZARD DATA

PRIMARY ROUTE OF EXPOSURE Eyes, Skin, Inhalation, Ingestion
 SIGNS & SYMPTOMS OF OVEREXPOSURE (ACUTE) Direct contact with eyes may cause redness, tearing and burning. Harmful if absorbed through the skin. Skin contact may cause redness, burning or drying. Inhalation of spray mist may cause respiratory tract irritation, drowsiness, dizziness, loss of coordination. Ingestion can cause irritation or burns of the mouth, nose, throat and stomach along with nausea and vomiting.
 SIGNS & SYMPTOMS OF OVEREXPOSURE (CHRONIC) Harmful if repeatedly absorbed through the skin.
 MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE Pre-existing skin and lung disorders.
 CARCINOGEN OR SUSPECTED CARCINOGEN INGREDIENTS: None

SECTION VII: EMERGENCY AND FIRST AID PROCEDURES

EYES: Flush with water for at least 15 minutes and call physician immediately.
 SKIN: Wash affected areas with soap and water. Launder contaminated clothing before reuse. If irritation persists call a physician.
 INGESTION: **DO NOT** induce vomiting. Call physician immediately.
 INHALATION: Remove to fresh air. Start artificial respiration if necessary. Oxygen may be administered. Call physician.

SECTION VIII: PERSONAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Not required under normal use conditions. Use with adequate ventilation.
 VENTILATION REQUIREMENTS: Normal
 EYE PROTECTION: Chemical Goggles Recommended
 PROTECTIVE GLOVES: Rubber/PVC Recommended
 OTHER PROTECTIVE CLOTHING: Impervious protective clothing appropriate to minimize contact.

SECTION IX: SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN Pick up on an absorbent material and put in suitable containers for proper disposal. Caution, slip and fall hazard.
 WASTE DISPOSAL METHODS: Dispose of in accordance with appropriate Federal, State and local regulations.

SECTION X: STORAGE AND HANDLING INFORMATION

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Wash thoroughly after handling. Direct spray away from face. Do not puncture or incinerate container. Do not store at temperatures exceeding 120°F.

DATE PREPARED 06/26/2012